

## WAXES POROUS SURFACE: 1ST APPLICATION

A long-lasting self-shining polish, with excellent resistance to wear and an optimum shine. Gives quality protection to flooring, as it prevents dirt entering the material, thereby facilitating general cleaning.

### USE

The wax, resin and natural oil-based product penetrates deep into the pores of baked clay, rustic, or porous stoneware floors. It brings out the natural colour of the floor, giving it a silky shine that can be polished, and prevents slipping.



### HOW TO USE



#### PREPARATION AND QUANTITY

Use undiluted on a thoroughly clean and dry floor.



#### APPLICATION

Manual: Apply the product evenly using circular movements with a cloth or ball of cotton-wool.

With RUBILIM: Apply the product with a very soft sponge (Ref. 60958 for model 40N and 40-ND and Ref. 60978 for model 50N and 50-ND).



#### FINISH

Manual: leave to dry for approximately one hour and polish with a cloth.

With RUBILIM: leave to dry for approximately one hour and shine with a natural-fibre brush (Ref. 60959 for model 40N and 40-ND and Ref. 60979 for model 50N and 50-ND). If required, a second layer may be applied after 8 hours. For maintenance, only POROUS SURFACE WAX: MAINTENANCE is required, diluted in the washing water.

### TECHNICAL SPECIFICATIONS



#### CHARACTERISTICS AND YIELD

- A solvent-based wax paste, made of a mixture of waxes and paraffin with aromatic solvent.
- Contains hydrodesulphurised heavy naphtha (petroleum).

#### Yield:

65-108 Sq.ft. / 0.2 gl. (6-10 m<sup>2</sup>/l.)



#### PRECAUTIONS

Do not ingest. Inflammable. Toxic to aquatic organisms. Harmful: may cause lung damage if ingested. In case of fire, use sand, soil, chemical powder or foam.

Never use water.

In case of ingestion do not provoke vomiting: seek medical help immediately, showing the label or packaging.

	PACKAGING FOR SALE TO PUBLIC				INDUSTRIAL AND WHOLESALE PACKAGING (STANDARDISED METAL DRUM)			
	0,2 gl - 1 L	1,1 gl - 5 L	5 gl - 25 L	10 gl - 50 L	20 gl - 100 L	40 gl - 200 L		
<b>Ref.</b>	20980	20981	21957	21958	-	-		
	8413797209808	8413797209815	8413797219579	8413797219586	-	-		

APPLICABLE ON	STAINS TYPES
Baked clay, mosaic, facing brickwork, klinker and concrete.	Wax.