

# WAXES POROUS SURFACE: MAINTENANCE

35



Water and detergent-resistant waxy emulsion. Specially formulated to protect, shine, and maintain stoneware and baked clay flooring, previously treated with WAXES POROUS SURFACE: 1ST APPLICATION.

## USE

For perfect maintenance of floors waxed with WAXES POROUS SURFACE: 1ST APPLICATION. Applicable to all types of porous ceramic. Its wax, polymer and resin-based composition guarantees a perfect application, with excellent resistance to water and detergents.

## HOW TO USE



### PREPARATION AND QUANTITY

Use 3 or 4 capfuls of product diluted in a bucket of water.



### APPLICATION

Apply with a mop.



### FINISH

Leave to dry normally.

## TECHNICAL SPECIFICATIONS



### CHARACTERISTICS AND YIELD

Waxy emulsion, made of waxes and surface-active agents in water. The product cannot be removed using water.

**Ph:** 8.0-9.0

**Density:** 1,5 Lb / 0,2 gl. (0,670 kg/l)

**Yield:**

40-60 m<sup>2</sup>/l diluted in water.  
1957-2935 Sq.ft. / 0,2 gl.



### PRECAUTIONS

Do not ingest.  
Keep out of the reach of children.

	PACKAGING FOR SALE TO PUBLIC		INDUSTRIAL AND WHOLESALE PACKAGING (STANDARDISED POLYURETHANE DRUM)			
	0,2 gl - 1 L	1,1 gl - 5 L	5 gl - 25 L	10 gl - 50 L	20 gl - 100 L	40 gl - 200 L
<b>Ref.</b>	20982	-	21961	21962	-	21964
	8413797209822	-	8413797219616	8413797219623	-	8413797219647

#### APPLICABLE ON

Baked clay, mosaic, facing brickwork, klinker and concrete.

#### STAINS TYPES

Wax.